

# High Velocity™ Touch Free In-Bay Vehicle Wash System



## STANDARD FEATURES

- Touch Free Design
- Wash View Controller w/ Exclusive Wash View Remote Software
- All Stainless Steel Wall Mounts, Rails, Carriage & Trolley Assemblies
- Direct Drive Utilizing Variable Frequency Drives
- Pumping Station All Stainless Steel w/ Either CAT or General Pump Standard
- Deluxe Image Package
- ETL Approved
- Resource Conservation System
- Two Step Solutions Ready
- Modem w/ Fault Paging
- High Pressure Under Carriage and Rocker Blasters
- Direct Feed Solutions System
- Triple Pass Technology
- Washes Dual Wheel Trucks
- Integrated Security Systems

## OPTIONS

- Deluxe Door Controls
- Drying Systems
- Free Standing Frame
- Spot Free (RO) Systems
- Cold Climate Package
- Tri-Color Foam
- Reclaim System Adapter
- Directional In-Bay Signs
- Exterior Signage and Clearance Bar

The Washworld High Velocity™ Touch Free In-Bay Automatic Wash is truly the best of all worlds. Cutting edge technology and proven performance, all at a price you simply cannot beat. With dozens of standard features, premium components, factory testing and 24/7 technical support, Washworld leads the way.



1755 E. Matthew Drive • DePere, WI 54115  
 920.338.9278 • 888.315.7253  
[www.washworldinc.com](http://www.washworldinc.com)



## Specifications

### Building Dimensions (Does not include dryer, obstructions, etc.)

<b>Height</b>	Wall Mount	10'-4" minimum (custom) 11'-4" standard
	Floor Mount	11'-4" standard
<b>Width</b>	Wall Mount	13'-4" minimum to 18'-0" maximum
	Floor Mount	14'-0" minimum (no maximum)
<b>Length</b>	Wall Mount	24'-10" minimum w/ optional 24' Rails
	Floor Mount	26'-10" minimum w/ standard 26' Rails

### Utility Requirements (Does not include dryer, RO, etc.)

- Air**                    5 CFM @ 100 PSI minimum
- Water**                5 GPM @ 35 PSI minimum at pump station
- Electrical** (all voltages 3 phase, 4 wire (neutral) and ground)

#### **High Velocity Electricity Requirements**

Voltage	UCC Cabinet	High Velocity Pump Station	Optional Cold Climate Package
208	23 Amps	73 Amps	14 Amps
230	20 Amps	62 Amps	12 Amps
460	n/a	31 Amps	n/a