

High Velocity™ Spot Free Water Conditioning System

STANDARD FEATURES

- Stainless Steel Mounted Stand
- 4" x 40" Thin Film High Efficiency Membrane(s)
- Audible and Visual Alarms
- Continuous TDS Monitoring
- Carbon Pre-Filter with Automatic Backwashing
- Microprocessor Controls
- Inlet, Pump and Membrane Pressure Gauges
- Stainless Steel Membrane Housings
- ETL Approved
- Automatic Inlet Water Shut-Off Valve
- Permeate and Concentrate Flow Meters
- Programmable Membrane Flushing
- Cartridge Style Pre-Filters

OPTIONS

- Water Storage Tanks (UV Rated)
- RE-Pressurization Pumps
- Water Softening Systems
- 2400, 4800, or 7200 Gallon Per



Every Washworld Premium Series Spot Free (Reverse Osmosis) System is manufactured for maximum efficiency. Washworld systems begin where most end. All stainless steel frame assemblies. Carbon pre-filters w/ 5 micron cartridge style filters and thin film high efficiency membranes in stainless steel housings...standard! Low level protection, fresh water by-pass and of course world class Washworld support.

WASHWORLD®

1755 E. Matthew Drive • DePere, WI 54115
 920.338.9278 • 888.315.7253
www.washworldinc.com



Model (Gallons Per Day)

	2400	4800	7200
# of Membranes	1	2	3
Pump H.P.	3/4 H.P.	1 H.P.	1-1/2 H.P.
Inlet Size	3/4" NPT	3/4" NPT	3/4" NPT
Permeate Size	1/2" NPT	1/2" NPT	1/2" NPT
Drain Size	1/2" NPT	1/2" NPT	1/2" NPT
Feed Flow	2.8 GPM	4.8 GPM	6.8 GPM
Permeate Flow	1.7 GPM	3.4 GPM	5.1 GPM
Drain Flow	1.1 GPM	1.4 GPM	1.7 GPM
Dimensions (Stand)	2'-0"x 2'-0"x 5'-6"	2'-0"x 2'-0"x 5'-6"	2'-0"x 2'-0"x 5'-6"
Approx. Weight	150#	180#	210#
Electrical Req'd	230VAC - 1 Phase - 7.5Amps and 120VAC - 1 Phase - 15Amps	230VAC - 1 Phase - 9.5Amps and 120VAC - 1 Phase - 15Amps	230VAC - 1 Phase - 11Amps and 120VAC - 1 Phase - 15Amps
Cartridge Style Pre-Filter Size	2.5"x 20" 5 Micron	2.5"x 20" 5 Micron	2.5"x 20" 5 Micron